3m sidewall 100%

Artwork Checklist

1/ Fonts to outlines?
2/ Pantones refs?
3/ Photos embedded?
4/ Visual supplied?

Notes:
Layers:
Open layers window.
Click on the appropriate layer to select size and then click visibility to view.

Material: we start with white material and print all colour in. The back of the material appears whitish when printed.

Bleed:Template includes bleed.
The Illustrator guides show finished size. The two vertical guides indicate where velcro is stitched on to the wall. Keep text to the right of these guides.

Size: Templates set to 100% except where indicated.

Colour: use CMYK values and leave Pantone Colour references where applicable. We will do our best to get as close as possible.
Dye sublimation tends to exaggerate majenta and cyan, so please indicate nearest PMS colour where possible.

Photoshop Elements:
The higher the resolution, the better the results. Save any Photoshop elements as Photoshop with transparent background NOT as jpeg. Do not flatten any layers.

Font usage:
Turn ALL fonts to outlines.

Software:
We prefer Adobe Illustrator files saved as an.eps or as a print quality pdf. We currently use Cloud based Adobe so the newest version will always be installed. If you are using In Design, export the file as a print quality pdf. Package the fonts and the links and send all together as we may need to do some colour correction.

Visuals:
Please supply as a separate document a visual of all printed walls indicating position to be used